





It's not a sports bike, it's a Race Machine.



**INRRC CHAMPION 2017** 

we've had one aim, and an aggressive track presence culminate to ensure that the RTR 160 4V is the first across the finish line.

For 10 years The RTR 160 4V is the latest in the line of accomplished racing Apaches. Raw racing power

## 1. Ultimate racing power



## INMRC Championship Winning Engine

The Oil-cooled 4 Valve, short stroke racing engine produces 16.5 PS @ 8,000 RPM. The power plant is derived from the 6-time INMRC winning RTR 165 prototype.



0-60km/h in 4.73 sec\*

## Racing Double-Barrel Exhaust

The exhaust has been meticulously tuned to produce the signature Apache racing sound.

# 2.Razor-sharp 3.Streetfighter handling styling



#### Patented Racing Synchro Stiff Chassis

The unique Double Cradle Split Synchro STIFF Chassis provides increased stiffness for sharp cornering.



### Digital Racing Console

The high-tech race computer records top speed, the 0-60 time and provides a gear shift indicator to the racer.



#### Roto-Petal Disc Brake

The design, drastically reduces braking distance on the track while allowing for faster heat dissipation.



#### Streamlined Muscular Tank

The tank has been aerodynamically modelled to cut through the wind. The chequered flag graphics pay homage to the dominance of the Apache on the track.



#### Race Tuned SHOWA Monoshock

The compression and rebound damping have been precision tuned on the race track along with experts from SHOWA -Japan. The set-up gives racers confidence while carrying higher cornering speeds.



#### Imposing Headlamp

Aggression meets functionality with the High-intensity LED Position Lamps with a unique fang design.

#### TVS APACHE RTR 160 4V SPECIFICATIONS >

Figures highlighted in red indicate RTR 160Fi 4V specifications.

ENGINE & HANDLING	
Туре	SI, 4 stroke, Oil cooled
Engine Capacity	159.7 cm <sup>3</sup>
Maximum Power	12.14 kW @ 8000 rpm (16.5 PS @8000 rpm)
	12.35 kW @ 8000 rpm (16.8 PS @8000 rpm)
Maximum Torque	14.8 Nm @ 6500 rpm
Fuel Supply System	Carburetor
	Fuel Injection

4 valves Starting **Electric & Kick Start** 

Power to Weight Ratio 0.0849 kW/kg 0.0843 kW/kg

5 speed gearbox Gearbox Monoshox Rear Suspension

Double Cradle Split Synchro STIFF Frame Front Suspension Telescopic Forks

**FUEL TANK CAPACITY** 

Valve Per Cylinder

12 L Full

DIMENSION

Height 1050 mm Length 2050 mm Width 790 mm Wheelbase ~1357 mm **Ground Clearance** 180 mm Saddle Height 800 mm ELECTRICAL

Battery AHO 12V, 35/35W HS1 bulb, with all-time Headlamp ON LED position lamp

> AHO 12V, 60/55W H4 bulb, with all-time ON LED position lamp

12V, 9Ah

'DOT3/DOT4

WHEEL AND TYRE

90/90-17 49P Tubeless Tyre Size (front) Drum - 110/80-17 57P Tubeless Tyre Size (rear) Disc - 130/70-17 M/C 62P Tubeless Disc - 130/70-17 M/C 62P Tubeless

BRAKE

270mm dia Petal Disc Front Drum - 130mm dia Drum Rear Disc - 200mm dia Petal Disc 200mm dia Petal Disc

Brake Fluid

WEIGHT Drum - 143 kg Kerb Weight Disc - 145 kg (with 90% fuel & tool kit) Disc - 147 kg

Above specifications are certified as per BS IV vehicle norms. "Under standard test conditions.

AVAILABLE IN >



RR Red



Racing Blue



Racing Black

TVS TVS MOTOR COMPANY

TVS Motor Company Limited. P.B. No.4, Harita, Hosur - 635 109 Tamil Nadu, India. Tel: +91 (4344) 276780. Fax +91 (4344) 276878 / 277311.